

**KOUPACÍ JEZÍRKA,
BIOBAZÉNY
A VEŘEJNÁ KOUPALIŠTĚ**
PŘÍRODĚ BLÍZKÁ ŘEŠENÍ

24|1|2024

Dipl. Ing. Stefan Bruns, Německo

**VEŘEJNÁ PŘÍRODNÍ KOUPALIŠTĚ
VE SVĚTĚ – ZPŮSOBY ČIŠTĚNÍ
VODY, DESIGN, PŘEDPISY
VČETNĚ HYGIENICKÝCH**



ASOCIATE BIOBAZENU A JEZIREK

24.01.2024



OFFICE PRESENTATION - POLYPLAN/KREIKENBAUM



SERVICES TO IMPLEMENT SUSTAINABLE PROJECTS

The Polyplan - Kreikenbaum Group

- a young at heart team with 30 years
of professional experience

... and always innovative ideas



LANDSCAPE ARCHITECTURE

City planning, campus planning
Waterfronts & Lakes
Urban lakes, water playgrounds

ENVIRONMENTAL ENGINEERING

Public outdoor and indoor swimming pools
Lake restoration and urban waters
Retention soil filter
Modulation of hydraulics and aquatic ecosystems
Water playgrounds
Technical and biological water treatment
Engineering biology
Retention soil filter

TGA

Office buildings, residential complexes
Sustainable energy management
Local heating concepts
Integrative residential construction energy planning

PROJECT SUPERVISION

Support in water management
Database-based project communication (DASEE, DANA)
Energy controlling via IOT based systems



OFFICE PRESENTATION CREDENTIALS



Aabach Talsperre (200 ha)
Offenbach (Frankfurt)




Maschsee (80 ha)
Hannover, Redevelopment concept



Friedhofsgewässer (Water network)
Bremen



Potsdamer Platz, water technology,
Berlin



Auweicher Fulda
Fulda



Südseecamp
Wietendorf



Arkadien Settlement project
Winnenden, Gewässer

OFFICE PRESENTATION

REFERENCES

NATURAL BATHS



Freibad Tessin
Tessin



NSP Ruds Vedby Kiddy pool of the public
Dänemark



OFFICE PRESENTATION

REFERENCES

CHLORINATED POOLS



Melbbad, Bonn, Germany




Aqualaazium
Germany, Hannover



Faces of an NSP



PUBLIC NSP IN THE WORLD



Author: Stefan Bruns; Stefan.Bruns@polyplan-gmbh.de


PUBLIC NSP IN THE WORLD




POLYPLAN
KREIKENBAUM



PUBLIC NSP 2019



Potential of public NSPs in Germany





1. Nature Awareness
2. Energy resources
3. Nature based Solutions
4. Better CO2 balance
5. No Alergica
6. No dangerous chemical products (Chlorine gas)
7. No chemical by-products
8. Attractive landscape element also beside the season

1. Less biofilm
2. Less human maintenance effort
3. always the same water quality
4. Less hygienic measurements
5. Less parasites



ECONOMICAL ARGUMENTATION - PRO AND CONTRA



1. Savings of investment cost 15-40%
2. Saving of energy costs 20-80%
3. Saving of water recourses 60 l/bather and day
4. Better funding options

1. Saving of cost for analyses 6000-10.000 €/year
2. Less human recourses



1. Water temperature $< 27^{\circ}\text{C}$
2. Water transparency $> \text{Bottom}$
3. Max. nominal bathers 1
Bather/ m^3/d
4. No max. Bather limitation/day
5. Frequency of Health
measurements 7-14 days



PUBLIC NSP DEMANDS TO THE WATER TRANSPARENCE

1. Always up to the bottom

2. 0,5-2 Fnu

'Clear and beautiful:' Edmonton says chemical-free swimming pool first in Canada

The Borden Natural Swimming Pool uses plants, zooplankton and granite rather than chlorine or salt to filter its water



The Canadian Press
Rob Drinkwater

Published Jul 20, 2018 • Last updated Jul 20, 2018 • 3 minute read

[Join the conversation](#)



Members of the public float in the outdoor natural pool in Edmonton, Alta., on Monday, July 16, 2018. JORG XMIT: EDM101 PHOTO BY JASON FRANSON/CANADIAN PRESS

JUMPING



PUBLIC NSP IN THE WORLD



POLYPLAN
KREIKENBAUM





1. Lifeguards are mandatory.
2. The pool should be planned in such a way that it can be seen from one position.
3. Normally, the baths work with one lifeguard of up to about 300 bathers.
4. With 3000 bathers, about 3 lifeguards are used.

INTRANCE REGULATION

1. FREE ENTRY
2. AUTOMATIC PAID ENTRY
3. MANUAL ENTRY TO BE PAID
4. ANNUAL PASSES FOR YEAR-ROUND USE
OF THE FACILITY



OFFICE PRESENTATION

REFERENCES

NATURAL BATHS



Freibad Ennigerloh
Ennigerloh



OFFICE PRESENTATION/TEAM/EXPERIENCES

OFFICE PRESENTATION – QUALIFICATIONS/REFERENCES

LOT 1 - NATURAL POOLS



Naturfreibad Bingen
Bingen am Rhein



Nordseelagune Burhave
Burhave



TOP 6: PLANUNG UND KONZEPT

NSP BREMEN, GERMANY INTENSIVE 3000 BATHERS A DAY



Impressions

NSP Floating Pool Aarhus, Denmark, extensive 4000 Bathers a day
24.000 m³



Floating Pool Aarhus

Unique Concept Design "Basin in treated Cover Basin"
The attractive harbor pool in Aarhus consists of a spacious platform in which 3 pools are embedded.

The edge area facing away from the pier has a second deck level which creates a multi-dimensional character and many niches are built up.

The bath is operated according to the EU bathing water directive. The pools (kiddy pool, swimmer pool and jumper pool) are located in the swimming deck. The wall and bottom of the basins are framed by a net. That means the basins are hydraulic open against the Cover basin.

Place:

Teknik og Miljø Center
for Byens Anvendelse
Aarhus Kommune
Kalkværksvej 10
8000, Aarhus C

Contractor: AarhusKommune Team
Byggemodning

Period:

2017 - 2018

Phases:

1-9

Honrar:

6.000.000,00 €
2.000.000,00 € (Polyplan+Polycon)

Impressions

NSP Floating Pool Aarhus, Denmark, extensive 4000 Bathers a day
24.000 m³



Straussvej Courtyard



Client:
KØBENHAVNS KOMMUNE

Location:
Copenhagen, Denmark


Execution time:
2019 to 2020

Service phases:
1 - 4


Opening:
2020

Building costs:
450,000 Euro

Planning Fees:
32,000 Euro



We used our numerical simulation tools to design the water treatment system and positioned it in close coordination with the open space planners and the client. According to model calculations, phosphorus concentrations of 5 to 31 µg/l Ptot-P occur. So far, the measured concentrations were 5 – 15 µg/l.




Impressions



Sponge City project Metro station Budova

Urban pool with natural water treatment

Surface 1120 m²



Version 1: Natural pool organic design cost effective

Impressions

NSP Floating Tessin, Germany, extensive use

4000 bathers a day

3400 m³



Tessiner Südsee



The Pool is located in an area just south of the existing sports and leisure complex in the area of Sankt-Jürgen-Straße. It covers an area of approximately 1.7 hectares.

The lake was used as a bath with biological water treatment, gem. FLL 2011 running and the filter surfaces are located in the eastern part of the site.

The lake has an area of approx. 2.500m² and a water depth of up to 4m.

In the eastern area, a 25m pool with 4 lanes is integrated. In the western shore area, a bridge and a water slide, as well as two smaller ones Basins are each arranged with approximately 50m² of water surface.

In the south and north beach areas with a total area of approx. 1.400m² border the bathing lake.

Places:

Tessin

Contractor:

City of Tessin
Alter Markt 1
18195 Tessin

Period:

2010 - 2012

Phases:

1-9

Construction costs:

2,0 Mio. Euro


Planning fee:

150.000 Euro

honorary regulatio hoai:

Part II and Part IV, General
Planning

Hygienic limits, FLL Regulation




Wy water treatment





Water treatment

Analogy disinfected pool versus NSP



Impact of Zoo plankton against Giardia and Protozoa ... a positive factor against chlorine disinfection?

Impact of Zooplankton Grazing on the Existence, Viability, and Infectivity of the Protozoan Pathogens *Cryptosporidium parvum* and *Giardia lamblia*; S. J. Connelly,^{1*} E. A. Wolyniak,² K. L. Dieter,^{1†} C. E. Williamson,¹ and K. L. Jellison²; *Department of Zoology, Miami University, Oxford, Ohio, 1 and Department of Civil and Environmental Engineering, Lehigh University, Bethlehem, Pennsylvania 2*; Received 30 May 2007/Accepted 6 September 2007

Internal disinfection

A study of 13 public swimming pools was carried out in Germany, with the aim of recording semi-qualitative data on the zooplankton population. The tests detected the presence of the genera Flagellata, Ciliata, Rotatoria, Cladocera and Copepoda. A low filtration rate was identified if values were between 0 and 2.5 times per day, while a comparatively high filtration rate was characterized by values between 2.6 and 10 times per day. The maximum filtration rate occur with approx. 20 m³/m³/d, the 90% occur with 0.04 m³/m³/d



External disinfection

Disinfection via external water treatment is crucial in ensuring the safety of the system for both users and the environment.

1 to 3 Log steps



In-situ disinfection in baths with biological water treatment


Interior disinfection in bathrooms with biological water treatment

Filtration by zooplankton $0.04 - 24 \text{ m}^3/\text{m}^3\text{tank volume/day}$

The filtration line is higher at higher bath loads, because the nutrient supply is then better

The zooplankton filters where it finds food (algae, bacteria, foursores, etc.) Compared to chlorine, it is therefore a "smart disinfectant"

The presence of zooplankton is not easy to measure



In-situ disinfection in baths with chemical/physical water treatment

Disinfection with chlorine is effective against many viruses and bacteria within minutes.


It has almost no effect on protozoans and on viruses with a stable envelope. Regarding the latter, there is little research

The presence of chlorine is easy to measure

Water treatment

different Ex-situ Water treatment groups


Aquatic systems



- **Hydrobotanik**

1. PT elimination by macrophytes 30-40%
2. E. coli elimination via zooplankton filtration
3. Habitat for zooplankton


Biofilter systems



- **Constructed Wetlands**

1. PT Elimination by Biofilm 10-20%
2. E. coli Elimination 1...3 Log steps

Biofilter systems



- **Substrate filter**

1. PT Elimination by biofilm 10-20%,
2. E. coli Elimination 1...3 Log steps

Water treatment different Ex-situ Water treatment

Art der Filtration Anforderung		Hydrobotanische Anlagen	
		submers	emers
Aufbau			
Höhe Wassersäule		≥ 0,80 m	0,10 – 0,50 m
Dicke der Substratschicht		10 – 20 cm	10 – 30 cm
Gefälle auf Filtersohle		—	—
Verhältnis von Mächtigkeit der filterwirksamen Schicht zum horizontalen Abstand der Dränagen		—	—
Material			
Korngrößenbereich ¹⁾	Pflanzenstandort	≤ 8 mm	
	Filter	—	—
Überkorn (Filter)		—	—
Anteil an abschlämmbaren Teilen		≤ 10 %	
Frostbeständigkeit		muss gegeben sein	
Pflanzenverträgliche Eigenschaften des Substrates		- frei von pflanzenschädlichen Stoffen - keine negativen Wechselwirkungen zwischen Substrat und Pflanze - gut durchwurzelbar	
Toleranzen			
Schichtdickentoleranz		—	—
Ebenheit		—	—
maximale Setzungen nach 1-jährigem Betrieb		—	—
Kennwerte			
K _f -Wert in m/s		—	—
Nährstoffgehalt im Wasser C/N/P-Verhältnis		106/16/7	—
Beschickungshöhe Q _{max}		6 m³/(m² x Tag)	6 m³/(m² x Tag)
Eliminationsrate Phosphor		0,4	0,3
Eliminationsrate <i>E. coli</i>		0,1	0,1



<https://shop.fll.de/en/fll-english-publications.html>

Water treatment

Constructed wetlands (essentials)



WATER TREATMENT IN NATURAL POOLS IN GENERAL

Water Treatment – kindly supported by Mother Nature

Basically the water treatment in a natural bath is very simple.

Leave the chemicals out and take natural materials in.

We work with a development of our own, the

Neptun® Percolating Filter

Water is oxygenated by being sprayed via sprinkler nozzles (this is also an impressive and at the same time relaxing picture for the guest)

While the water trickles down through the filter substrate pathogenic germs are being eliminated by physical and biochemical processes



The filter thus guarantees high operational reliability

Overflow water is captured in the wet filter pool which is cropped with water plants.




Water treatment

Constructed wetlands (essentials)




Ex-situ Phosphor reduction, Constructed wetlands (R&D)

Elimination of Phosphorus
4 mWc/d, 1,3 m Thickness



Elimination of Coliphages




Water treatment

Data Base Dana




- Database for approx. 80 Public NSP world wide 2005 - today



- All Parameters are described with regulations like DIN, EN...




- All sampling points are described in a scientific way




- Operation data
- Hygienic data
- Limnologic data

Water treatment

DANA 2.0 Projects, evaluation of 80 public and 60 privat NSP





POLYPLAN
KREIKENBAUM



Water treatment

DANA 2.0 Projects, evaluation of 62 public NSP






Hygienic Results

E.Coli Frequency of concentrations



E.coli Frequencies Basin water and Pure water 2005.. 2021



E.COLI [CFU/100 ML]

Frihamn, Gothenborg

Floating Pool



(Göteborg 2023)

Frihamn, Gothenborg

Floating Pool



(Göteborg 2023)

Naturfreibäder

Frihamn, Gothenborg
Floating Pool



(Göteborg 2023)

Naturfreibäder

Frihamn, Gothenborg

Floating Pool



(Göteborg 2023)



Frihamn, Gothenborg

Floating Pool



Frihamn, Gothenborg

Floating Pool



(Göteborg 2023)

Frihamn, Gothenborg

Floating Pool



(Göteborg 2023)

Frihamn, Gothenborg

Floating Pool



Waldimir

POLYPLAN 
KREIKENBAUM

Thanks so much for attention



Let's swim together

Bruns@polyplan-kreikenbaum.eu

Water treatment

EU Project Digital intelligence HUB DIH4 CPS



Fostering DIHs for Embedding Interoperability
in Cyber-Physical Systems of European SMEs



info@dih4cps.eu



HOME

PROJECT

PARTNERS

DIH NETWORK

APPLICATION EXPERIMENTS


OPEN CALL

NEWS

DOCUMENTS



CYBER-PHYSICAL SYSTEM



Im Rahmen von DIH4CPS wurde eine Shrimp-Detektion mittels neuronaler Netze implementiert.

Es wurden zwei Basismodelle zur Objekterkennung in Bildern verwendet:
[YOLOv5 von Ultralytics](#) und [Tensorflow Object Detection API](#) (EfficientDet).

POLYPLAN 
KREIKENBAUM

Water treatment

In-Situ Desinfektion, AI-Model

Artificial intelligence = structures that are not programmed, but derived from algorithms = machine learning

The algorithm is trained to derive the relevant structures that are necessary to solve given problems. (Deru and Ndiaye 2019, 17) A distinction is made between the following three forms of machine learning:



Ex-situ Virus and Bacteria reduction, Constructed wetlands (R&D)



Mittlere Keimzahlreduktionen in Log Stufen (95th confidence interval)

Barrier		Bakteriophage MS2 (qPCR)	Bakteriophage MS2 (PMA pre-treated qPCR)	<i>Enterococcus faecalis</i> (culture assay)	<i>Saccharomyces cerevisiae</i> (culture assay)
NF	Neptune filter	1.35 (1.05, 1.82)	0.83 (0.44, 1.64)	1.48 (1.36, 1.60)	1.69 (1.54, 1.85)
Hydrobotanik + Überstauter Substratfilter		2.35 (2.21, 2.52)	1.76 (1.55, 2.02)	1.79 (1.75, 1.84)	1.84 (1.63, 2.01)
UV1 (nach Neptunfilter)		0.73 ^b (0.13, 1.40)	0.62 ^b (-0.24, 1.18)	> 4.02 (3.66, 4.62)	>2.83 (2.49, 3.33)
UV2 (Nach Hydrobotanik+ Überstautem Bodenfilter)		>1.56 ^b (1.39, 1.69)	1.76 ^b (1.48, 1.96)	> 4.04 (4.01, 4.07)	>2.77 (2.51, 3.17)

Versuchsphase	Filterhöhe	Wassertemperatur	Hydraul. Belastung	Auslastung Anlage	<i>E. coli</i> - Ausgangskonzentration	Reinigungsleistung
Nr.	[m]	[°C]	[m ³ /m ² *d]	[%]	[MPN/100ml]	[%]
1	1,7	23	6	50	100	100
2	1,7	23	12	50	500	99,8
3	1,7	23	12	50	2000	99,9
4	1,2	23	12	50	500	99,3
5	1,2	23	12	50	2000	99,4
6	1,2	23	12	100	500	99,9
7	1,2	23	12	100	2000	99,8
8	1,2	23	24	100	500	99,4
9	1,2	23	24	100	2000	99,2
10	0,8	23	12	50	500	98
11	0,8	23	12	50	2000	97,7
12	0,8	23	12	100	500	99,7
13	0,8	23	12	100	2000	99,6

Reference I

NSP Bingen- semi artificial in Hillside, (Germany) intensive use

2000 bathers a day

Water volume 3200 m³



Reference I

- One Basin, Depths from 0.1 to 3.5 m
- 4* 25 m lines plus long range swimming 80 m
- Major focus: Family, morning swimmer, Childs, Youngsters, Schools



- | | | | |
|---------------------|----------------|--------------------|--------------------|
| 1 Eingang | 6 Rutsche | 11 Beachvolleyball | 16 Schwimmaufsicht |
| 2 Kleinkinderbecken | 7 Wasserlauf | 12 Kiosk | 17 Liegewiese |
| 3 Nichtschwimmer | 8 Aquakultur | 13 Duschen / WC | 18 Ausgang |
| 4 Schwimmer | 9 Neptunfilter | 14 Außenduschen | + Erste Hilfe |
| 5 Sprungbereich | 10 Uferfilter | 15 Umkleiden | F Feuerlöscher |



Reference II

NSP Tessin (Germany), very organic design

2000 bathers a day

Water volume 3200 m³



Reference II

- Sandbeaches surrounding
- One Basin, Depths from 0.1 to 3.5 m
- 4* 25 m lines
- Major focus: a Family one day Vacation Happening, schools, Tourists from the baltic sea



Tessiner Südsee



The Pool is located in an area just south of the existing sports and leisure complex in the area of Sankt-Jürgen-Straße. It covers an area of approximately 1.7 hectares.

The lake was used as a bath with biological water treatment, gem. FLL 2011 running and the filter surfaces are located in the eastern part of the site.

The lake has an area of approx. 2.500m² and a water depth of up to 4m.

In the eastern area, a 25m pool with 4 lanes is integrated. In the western shore area, a bridge and a water slide, as well as two smaller ones Basins are each arranged with approximately 50m² of water surface.

In the south and north beach areas with a total area of approx. 1.400m² border the bathing lake.

Places:

Tessin

Contractor:

City of Tessin
Alter Markt 1
18195 Tessin

Period:

2010 - 2012

Phases:

1-9

Construction costs:

2,0 Mio. Euro

Planning fee:

150.000 Euro

honorary regulatio hoai:

Part II and Part IV, General
Planning

Reference III

Bylderup (Denmark), very artificial

2000 bathers a day

Water volume 3200 m³



Reference III

- Stringent deckings are framing the pools
- Sandbeaches, small separate kiddy pool with sand beach
- 6* 25 m lines
- Major focus: Village pool. Swimmer, Family, schools, Tourists from summer camps



Natural Bad Ruds Vedby

Polyplan planned and advertised the entire open space planning and bathing technology. The bathroom is supervised by the Polyplan bath monitoring team and has a high operational safety.

Here it was about to discuss the first bath with biological water treatment in Denmark with the state health department and to obtain a special permit. After several hygiene workshops, all players agreed on the FLL guideline 2011. In addition, there is a requirement on the part of the operator to use as much electrical energy as possible. The maximum energy consumption should not exceed 12 kwh / d.

Places:

Ruds Vedby
4291, Denmark

Contractor:

Jesper Fussing Hjortgaard

Period:

2013 -2015

Phases:

1-8

Construction costs:

1,5 Mio. Euro



Impressions

NSP Bingen- semi artificial in Hillside, (Germany) intensive use
2000 bathers a day
Water volume 3200 m³



Impressions

NSP Kirchdorf- Low energy – extensive organic design – big water bodies – extensive use

1200 bathers a day

Water volume 4500 m³



Combination of Neptune and wet filters and hydro botany

Attractions such as a slide and water cannons complement large lawns and retreats for relaxing and playing. Active play areas, especially the offer for children, have been expanded. The integration of the club restaurant with a terrace directly on the water improves the quality of stay. The bank filtration is located in a part of the basin separated by bars. The cleaning performance is achieved here with special plants and drained water drainage. The neptune

Floor filter has a high disinfection capacity and thus ensures a high level of hygienic operational safety and very clear water. The combination of these filter systems, with their specific cleaning performance and the connection with intelligent measurement and control technology, guarantees permanently optimal water quality.

Project location:

Diepholz district in Lower Saxony

Client:

Consolidated community of Kirchdorf

Execution time:

2002-2003

Work phases:

1-9

Building-costs:

360,000 euros, plus 120,000 euros personal contribution

Fee:

80,000 euros

Size:

3,500 sqm

Impressions

NSP Edmonton- extreme artificial design – big water bodies – semi
Intensive use

1200 bathers a day

Water volume 1600 m³



NSP, Natrual Swimming Pool Edmonton

The Borden parc Project has been realized by the partners GH3 and Polyplan. GH3 was responsible for the landscape and Building design. Polyplan was responsible for the Pool function, the water treatment, pump and pipe design and for micro controller system.

Today Polyplan monitor the system over the DANA platform and provide the back ground service for the pool operators on side.

Place:
Edmonton

Contractor:
Stadt von Edmonton
10111-104 Avenue NW
Edmonton, Mr. Robb Heit

Period:
2013 - 2018

Phases:
1-9

Construction costs:
6,0 Mio. CAD

Impressions

NSP Ennigerloh- semi artificial design – semi Intensive use

1500 bathers a day

Water volume 2700 m³



New planning of the swimming pool Ennigerloh

The swimming pool Ennigerloh is to be re-designed into a bath with biological water purification.

In addition to the renovation of the existing pools and buildings, the attractiveness of the outdoor pool is the focus.

The basic pool types and uses will continue to be offered and complemented by an extended non-swimmers area and beach area as well as a new jump facility and a slide. To increase the bathing pleasure and full deoletion of the bathing season, the pool water should be heated. The prerequisites and services which the outdoor pool must fulfill after the refurbishment are summarized in a specification, which is attached as an annex.

Place:
Ennigerloh

Contractor:
Business and spa operation
Marktplatz 1
59320 Ennigerloh

Period:
2019 - 2020

Phases:
1-9

Construction costs:
2,0 Mio. Euro

Planing fee:
380.000 Euro

honorary regulatio hoai:
Part II and Part IV
General Planning

Impressions

NSP Froschloch - artificial design – Intensive use

3500 bathers a day

Water volume 890 m³



Natural Outdoor Swimming Pool Froschloch

The outdoor swimming pool was in its former state in need of renovation. The need of renovation concerned the basin substance (leaks), the technical water treatment (Filter, disinfection, basin hydraulics), as well as the free surfaces.

The water treatment system of the natural outdoor swimmingpool Froschloch is a ground filter called Neptune. It is covered in swamp and ripe plants for aesthetics. The Water treatment area is 1200 m² big and is designed for 1700 visitors.

In 2015 Polyplan was awarded with the international pondy award 2015 by the

Places:

Schwimmweg 2
44139 Dortmund

BContractor:

Sportwelt Dortmund gGmbH
Frau Heckmann

Period:

2007 - 2008

Phases:

1-8

Construction costs:

1,7 Mio. Euro

Planing fee:

280.000 Euro

honorary regulatio hoai:

Part 2, Part 4

